Canon

CORPORATE SOLUTIONS

Color
imageRUNNER®
LBP5960

SPECIFICATIONS

MAIN UNIT

Type:	Desktop Color Laser Printer
Printing Method:	Electrophoto Method (Color RAPID Fusing System™)
Developing System:	Dry Dual Component Developing System
Memory:	Standard 128MB RAM Maximum 384MB RAM*
Hard Disk Drive:	Optional 20GB

Network Interface

Connections:	Parallel Connector (IEEE1284 Compatible) 10/100Base-TX (RJ-45)
Other Interface:	USB 2.0 Hi-Speed/USB Full-Speed (USB 1.1 Equivalent)
User Interface:	LCD 16 Characters x 1 Line 10 LED Indicators 8 Operation Keys
First-Print Time:	7.5 Seconds (B/W) 9.0 Seconds (Color)
Warm-Up Time:	0 Seconds From Standby, 30 Seconds or Less After Powering On
Print Speed (B/W, Color):	30/30 ppm (Letter)
CPU:	PowerPC 750CXr (400 MHz**)
Command Language:	UFR II, PCL5c

Print Resolution

UFR II:	1200 x 1200 dpi*** (Super Fine Mode) 600 x 600 dpi (Fine Mode) 2400 dpi Equivalent x 600 dpi (Fine Mode)
PCL5c:	600 x 600 dpi (Fine Mode) 2400 dpi Equivalent x 600 dpi
Engine Resolution:	Up To 1200 x 1200 dpi

Printer Drivers

UFR II:	Windows® (Windows 2000/XP/Server 2003,Citrix MetaFrame), Macintosh® (OS 10.2.8 or later)
PCL5c:	Windows (Windows 98/Me/2000/XP/Server 2003,Citrix MetaFrame)
Halftone:	256 Gradations (Continuous-Tone)

Paper Sources

Standard:	230-Sheet Paper Cassette (20 lb. Bond) 90-Sheet Multi-Purpose Tray
Optional:	550-Sheet x Up To 3 Paper Cassettes
Maximum:	1,970 Sheets

Paper Sizes

Cassettes:	Ledger, Legal, Letter, Executive
Multi-Purpose Tray:	Ledger, Legal, Statement, Letter, Executive, Custom Sizes (Width: 3-7/8" to 5-3/4"; Length: 5-1/2" to 18"), Long Size Paper (Width: 8-3/8" to 11-3/4"; Length: 18" to 47-1/4") and Envelopes

Acceptable Paper Weight

Cassettes:	17 lb. Bond to 28 lb. Bond
Multi-Purpose Tray:	17 lb. Bond to 80 lb. Cover
Maximum Paper Size:	11" x 17" (305 x 457mm)
Output Capacity:	Approximately 250 Sheets (20 lb. Bond)
Paper Output:	Face-Down
Duplexing:	Standard Automatic Trayless Duplexing (Executive to 11" x 17")
Dimensions (H x W x D):	15" x 21-1/2" x 24" (Main Unit)
Installation Space (W x D):	21-1/2" x 35-7/8" (When Multi-Purpose Tray is extended)
Weight:	Approximately 114.6 lb. (52 kg)▲
Power Supply:	120V – 127V, 60Hz

Power Consumption

Operating:	Approximately 585W (Average)
Standby:	Approximately 29W (Average)
Power Save Mode:	Approximately 10W (Average)
Plug:	NEMA 5-15P
Toner (Estimated Yield):	Black: 10,000 Images at 5% Coverage▲▲ Full Color: 6,000 Images at 5% Coverage▲▲

Hard Disk KIT HD-98A

Main Unit

Paper Feeder Unit PF-98

OPTIONAL ACCESSORIES

Paper Feeder Unit PF-98▲▲▲

Paper Sizes:	Ledger, Legal, Letter, Executive, Custom Sizes (Width: 8-3/8" to 11-3/4"; Length: 8-3/8" to 17")
Paper Cassettes Capacity:	550 Sheets (20 lb. Bond)
Dimensions (H x W x D):	5-5/8" x 21-1/2" x 27-1/2"
Weight:	Approximately 24.3 lb. (11kg)

Other Optional Accessories
- Hard Disk Kit HD-98A
- Barcode Printing Kit A-98A
- Cabinet-W1
- Cabinet-X1
- Expansion RAM ER-128
- Expansion RAM ER-256

* One memory slot available for expanding memory.
** The upper limit of the frequency range.
*** If 1200 dpi print is selected, engine speed will slow down.
▲ Excluding the Toner Cartridges and Drum Cartridges.
▲▲ When printing letter-sized paper at 5% page coverage with the default print density settings.
▲▲▲ Up to three additional paper cassettes can be added.

Canon

*image*ANYWARE

1-800-OK-CANON
www.usa.canon.com

Canon U.S.A., Inc.
One Canon Park
Melville, NY 11747